

INTEGRITY® NITRILE EXAMINATION GLOVES

602-0184 - 602-0188

Quality Cobalt Blue Nitrile examination gloves that offer increased tensile strength and protection over Latex and Vinyl. Incredible Ultra-Thin Nitrile examination gloves specifically designed to offer increased comfort, flexibility & sensitivity.

FEATURES

- Powder-Free Nitrile, textured fingertips, 9.4" length
- Non-Sterile used in industry segments such as life sciences, medical device, R+D, academy and advanced materials
- Beaded cuff allows easy donning
- Ambidextrous
- Latex Free, 100% synthetic nitrile polymer
- AQL 1.5
- Lot traceable

PRODUCT CODE	SIZE
602-0184	XS
602-0185	S
602-0186	M
602-0187	L
602-0188	XL

Packaged: 200 pcs/box, 10 boxes/case, 2000 pcs/case



To request a quotation or for more information, please call **+1 512-713-0127**, email info@integritycleanroom.com or visit www.integritycleanroom.com.

IMPORTANT: This data sheet and its contents (the "Information") belong to Integrity Cleanroom or are licensed to it. No licence is granted for the use of it other than for information purposes in connection with the products to which it relates. No licence of any intellectual property rights is granted. The Information is subject to change without notice and replaces all data sheets previously supplied. The Information supplied is believed to be accurate but Integrity Cleanroom assumes no responsibility for its accuracy or completeness, any error in or omission from it or for any use made of it. Users of this data sheet should check for themselves the Information and the suitability of the products for their purpose and not make any assumptions based on information included or omitted. Liability for loss or damage resulting from any reliance on the Information or use of it (including liability resulting from negligence or where Integrity Cleanroom was aware of the possibility of such loss or damage arising) is excluded. © Integrity Cleanroom.

NITRILE EXAMINATION GLOVES | 5 APRIL 2020 3:54 PM



Integrity US
Round Rock, Texas



Integrity UK
Bury St Edmunds, Suffolk






Integrity DE
Nuremberg, Bavaria



DIMENSIONS

THICKNESS

		
2.7" +/- 0.39" 70 ± 10 mm	min. 9.4" (240 mm)	
3.1" +/- 0.39" 80 ± 10 mm	min. 9.4" (240 mm)	
3.7" +/- 0.39" 95 ± 10 mm	min. 9.4" (240 mm)	1 4 mils (0.11 mm)
4.3" +/- 0.39" 110 ± 10 mm	min. 9.4" (240 mm)	2 2 mils (0.05 mm)
4.3" +/- 0.39" ≥ 110 mm	min. 9.4" (240 mm)	3 2 mils (0.05 mm)

PHYSICAL PROPERTIES	UNAGED	AGED
Tensile Strength	min. 14 MPa	min. 14 MPa
Elongation	min. 500 %	min. 400 %
Strength at Break	min. 6N	min. 6N

Manufactured under ISO 9001, EN, SGS, CMCAS quality systems. Product quality tested in accordance with relevant ASTM and EN standards.



To request a quotation or for more information, please call **+1 512-713-0127**, email info@integritycleanroom.com or visit www.integritycleanroom.com.

IMPORTANT: This data sheet and its contents (the "Information") belong to Integrity Cleanroom or are licensed to it. No licence is granted for the use of it other than for information purposes in connection with the products to which it relates. No licence of any intellectual property rights is granted. The Information is subject to change without notice and replaces all data sheets previously supplied. The Information supplied is believed to be accurate but Integrity Cleanroom assumes no responsibility for its accuracy or completeness, any error in or omission from it or for any use made of it. Users of this data sheet should check for themselves the Information and the suitability of the products for their purpose and not make any assumptions based on information included or omitted. Liability for loss or damage resulting from any reliance on the Information or use of it (including liability resulting from negligence or where Integrity Cleanroom was aware of the possibility of such loss or damage arising) is excluded. © Integrity Cleanroom.



Integrity US
Round Rock, Texas



Integrity UK
Bury St Edmunds, Suffolk



Integrity DE
Nuremberg, Bavaria

